

RESERVE STUDIES | INSURANCE APPRAISALS | WIND MITIGATION



Prepared Exclusively for Bordeaux Village Association, No. 3, Inc.

As of 12-07-2023 | FPAT File# MUD2320925



Felten Property Assessment Team

866.568.7853 | www.fpat.com

RECAPITULATION OF MITIGATION FEATURES For 13601 Frigate Ct., Building M, Units 101M-106M, 203M-204M

1. Building Code: Unknown or does not meet the requirements of Answer A or B

Comments: The year of construction was verified as 1981 per Pinellas County

Property Appraiser.

2. Roof Covering: FBC Equivalent

Comments: The roof covering was replaced in 2017. The roof permit was confirmed

and the permit number is PER-H-CW17-00919. This roof was verified as meeting the building code requirements outlined on the mitigation

affidavit.

3. Roof Deck Attachment: Level C

Comments: Inspection verified 1/2" OSB roof deck attached with 8d nails at a

minimum 6" on the edge & 6" in the field

4. Roof to Wall Clips

Attachment:

Comments: Inspection verified hurricane clips fastened with a minimum of three

nails.

5. Roof Geometry: Other Roof

Comments: Inspection verified a gable roof shape.

6. SWR: Yes

Comments: SWR was verified at time of inspection. The Secondary Water Resistance

verified is a self-adhering peel and stick.

7. Opening Protection: None or Some Glazed Openings

Comments: No opening protection verified at the time of inspection.

Address Verification



Exterior Elevation



SUPPORTING DOCUMENTION OF WINDSTORM MITIGATION FEATURES LOCATED AT: 13601 Frigate Ct., Building M, Units 101M-106M, 203M-204M

FPAT File #MUD2320925

Exterior Elevation



Exterior Elevation





Exterior Elevation

SUPPORTING DOCUMENTION OF WINDSTORM MITIGATION FEATURES LOCATED AT: 13601 Frigate Ct., Building M, Units 101M-106M, 203M-204M

FPAT File #MUD2320925

Roof Permit Information

Record PER-H-CW17-009 Express Building Permit Record Status: Finaled	919:	
Record info ▼	Payments *	
Work Location		
13601 FRIGATE CT * Clearwater FL		
Record Details		
Replacing a water heater, A	AC unit or water soft	ener? Virtual inspections are now available for these permit types. <u>Learn more</u> .
Virtual inspections will be	available for more pe	ermit types soon.
Licensed Professional: THOMAS MILLARD OWEN STAG OWEN, THOMAS MILLARD ALBRIGHT ROOFING & CONTR CLEARWATER, FL, 33762 Phone:7275412949 BUILDING CCC1327605		Project Description: Online Building Permit RFCSH re-roof BLD "M-2 story 5/12 pt/ch-78 sq. remove existing roof and demaged decking as needed. Replace decking and re-roall as per code. Dy-in with GAF Weather/Watch Mineral Surface Less Barier Underlaymen FL#1 9487-R5 (4.1.5) and install GAF shingles FL# 10124-R17
View Additional Licensed Prof	essionals>>	
✓ More Details ☐ Additional Information Job Value(\$): \$26,000.00 ☐ Application Information		
☐ Parcel Information		
Parcel Number:023016103 Block:013	470131010 *	
	and the Management of	10347

Roof Construction

Roof Construction

Roof Construction







Roof Construction



Roof Construction







Roof Construction



Roof Construction









Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

1 7	2	1 7	
Inspection Date: 12-07-2023			
Owner Information			
Owner Name: Bordeaux Village Association	Contact Person: Scott Vignery		
Address: 13601 Frigate Ct., Building M, U	Home Phone:		
City: Clearwater	Zip: 33762	Work Phone: (727) 726-8000	
County: Pinellas		Cell Phone:	
Insurance Company:	Policy #:		
Year of Home: 1981	# of Stories: 2	Email: svignery@ameritechmail.com	

NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.

1	Public Code. We the twenty heilt is conding a mid the Floride Public Code (FPC 2001 or later) OP for home leasted in
Ι.	<u>Building Code</u> : Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in
	the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)?
[]	A. Built in compliance with the FBC: Year Built . For homes built in 2002/2003 provide a permit application with a date after
	3/1/2002: Building Permit Application Date (MM/DD/YYYY)
[]	B. For the HVHZ Only: Built in compliance with the SFBC-94: Year Built For homes built in 1994, 1995, and 1996
	provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY)//
[X	C. Unknown or does not meet the requirements of Answer "A" or "B"

2. **Roof Covering:** Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified.

2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance
[X] 1. Asphalt/Fiberglass Shingle	01-27-2017		2017	
[] 2. Concrete/Clay Tile				[]
[] 3. Metal				[]
[] 4. Built Up				[]
[] 5. Membrane				[]
[] 6. Other				[]

- [X] A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.
- [] B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.
- [] C. One or more roof coverings do not meet the requirements of Answer "A" or "B".
- [] D. No roof coverings meet the requirements of Answer "A" or "B".
- 3. Roof Deck Attachment: What is the weakest form of roof deck attachment?
- [] A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the field. -OR- Batten decking supporting wood shakes or wood shingles. -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.
- [] B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the field.-OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.
- [X] C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width). -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent

Inspectors Initials Property Address 13601 Frigate Ct., Building M, Units 101M-106M, 203M-204M, Clearwater

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

 [] D. Reinforced Concrete Roof Deck. [] E. Other: [] F. Unknown or unidentified. [] G. No attic access. 4. Roof to Wall Attachment: What is the WEAKEST roof to wall connection? (Do not include attachment of hip/valley jacks within 5 feet of the inside or outside corner of the roof in determination of WEAKEST type) [] A. Toe Nails	182 psf.	
 [1] F. Unknown or unidentified. [2] G. No attic access. 4. Roof to Wall Attachment: What is the WEAKEST roof to wall connection? (Do not include attachment of hip/valley jacks within 5 feet of the inside or outside corner of the roof in determination of WEAKEST type) [3] A. Toe Nails		ncrete Roof Deck.
 [] G. No attic access. 4. Roof to Wall Attachment: What is the WEAKEST roof to wall connection? (Do not include attachment of hip/valley jacks within 5 feet of the inside or outside corner of the roof in determination of WEAKEST type) [] A. Toe Nails		
4. Roof to Wall Attachment: What is the WEAKEST roof to wall connection? (Do not include attachment of hip/valley jacks within 5 feet of the inside or outside corner of the roof in determination of WEAKEST type) [] A. Toe Nails [] Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or [] Metal connectors that do not meet the minimal conditions or requirements of B, C, or D Minimal conditions to qualify for categories B, C, or D, All visible metal connectors are: [X] Secured to truss/rafter with a minimum of three (3) nails, and [X] Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. [X] B. Clips [X] Metal connectors that do not wrap over the top of the truss/rafter, and free of visible severe corrosion. [X] B. Clips [X] Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nai position requirements of C or D, but is secured with a minimum of 3 nails. [C] C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side, or [] Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a m		
5 feet of the inside or outside corner of the roof in determination of WEAKEST type) [] A. Toe Nails [] Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or [] Metal connectors that do not meet the minimal conditions or requirements of B, C, or D Minimal conditions to qualify for categories B, C, or D, All visible metal connectors are: [X] Secured to truss/rafter with a minimum of three (3) nails, and [X] Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. [X] B. Clips [X] Metal connectors that do not wrap over the top of the truss/rafter, or [] Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nai position requirements of C or D, but is secured with a minimum of 3 nails. [] C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. [] D. Double Wraps [] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of 1 nail on the opposing side, or [] Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of 1 nail on the opposing side, or [] Metal Connectors consisting of a singl	[] G. No attic access.	
Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or Metal connectors that do not meet the minimal conditions or requirements of B, C, or D Minimal conditions to qualify for categories B, C, or D, All visible metal connectors are: X Secured to truss/rafter with a minimum of three (3) nails, and X Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. X B. Clips Metal connectors that do not wrap over the top of the truss/rafter, or Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nai position requirements of C or D, but is secured with a minimum of 3 nails. D. Double Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side with a minimum of 1 nail on the oppo	5 feet of the inside	
top plate of the wall, or [] Metal connectors that do not meet the minimal conditions or requirements of B, C, or D Minimal conditions to qualify for categories B, C, or D. All visible metal connectors are: [X] Secured to truss/rafter with a minimum of three (3) nails, and [X] Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. [X] B. Clips [X] Metal connectors that do not wrap over the top of the truss/rafter, or [] Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nai position requirements of C or D, but is secured with a minimum of 3 nails. [] C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. [] D. Double Wraps [] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to both sides, and is secured to the top plate with a minimum of 1 nail on the opposing side, or [] Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of 1 nail on the opposing side, or [] Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of 1 nail on the opposing side, or [] Metal Connectors consisting of a single strap that wraps ove		russ/rafter anchored to top plate of wall using pails driven at an angle through the truss/rafter and attached to the
Minimal connectors that do not meet the minimal conditions or requirements of B, C, or D		
[X]Secured to truss/rafter with a minimum of three (3) nails, and [X]Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. [X] B. Clips [X] Metal connectors that do not wrap over the top of the truss/rafter, or [] Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nai position requirements of C or D, but is secured with a minimum of 3 nails. [] C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. [] D. Double Wraps [] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured to the wall on both sides, and is secured to the top plate with a minimum of the nails on each side. [] E. Structural Anchor boths structurally connected or reinforced concrete roof. [] F. Other: [] G. Unknown or unidentified [] H. No attic access [] B. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall on the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). [] A. Hip Roof [] Hip roof with no other roof shapes greater than 10% of the total roo		
[X]Secured to truss/rafter with a minimum of three (3) nails, and [X]Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. [X] B. Clips [X] Metal connectors that do not wrap over the top of the truss/rafter, or [] Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nai position requirements of C or D, but is secured with a minimum of 3 nails. [] C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. [] D. Double Wraps [] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured to the wall on both sides, and is secured to the top plate with a minimum of the nails on each side. [] E. Structural Anchor boths structurally connected or reinforced concrete roof. [] F. Other: [] G. Unknown or unidentified [] H. No attic access [] B. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall on the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). [] A. Hip Roof [] Hip roof with no other roof shapes greater than 10% of the total roo	Minimal conditio	ng to qualify for estagories P. C. or D. All visible metal connectors are:
[X] Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. [X] B. Clips [X] Metal connectors that do not wrap over the top of the truss/rafter, or [] Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nai position requirements of C or D, but is secured with a minimum of 3 nails. [C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. [D. Double Wraps [Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured to the wall on both sides, and is secured to the top plate with a minimum of 1 nail on the opposing side, or [Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured to the wall on both sides, and is secured to the top plate with a minimum of 1 nail on the opposing side, or [Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or [Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or [Metal connectors consisting of a		
 [X] Metal connectors that do not wrap over the top of the truss/rafter, or [] Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nai position requirements of C or D, but is secured with a minimum of 3 nails. [] C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. [] D. Double Wraps [] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side. [] E. Structural Anchor boilts structurely connected or a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side. [] E. Structural Anchor boilts structurely connected or reinforced concrete roof. [] F. Other: [] G. Unknown or unidentified [] H. No attic access A line from shape specified or carports that are att		Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe
[] Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nai position requirements of C or D, but is secured with a minimum of 3 nails. [] C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. [] D. Double Wraps [] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side, or [] Metal Connectors consisting of 2 separate straps that are attached to the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side, or [] Metal Connectors consisting of 2 separate straps that are attached to the truss/rafter, is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the ross/rafter is secured with a minimum of 1 nail on the opposing side, or [] Metal Connectors consisting of 2 separate strap wraps over the top of the truss/rafter is secured with a minimum of 1 nail on the opposing side, or [] Metal Connectors consist		
Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. [] D. Double Wraps [] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. [] E. Structural Anchor bolts structurally connected or reinforced concrete roof. [] F. Other: [] G. Unknown or unidentified [] H. No attic access [] Mat is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall or the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). [] A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: ; Total roof system perimeter: Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft [X] C. Other Roof Any roof that does not qualify as either (A) or (B) above. [X] A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss.	[] N	Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail
minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. [] D. Double Wraps [] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. [] E. Structural Anchor bolts structurally connected or reinforced concrete roof. [] F. Other: [] G. Unknown or unidentified [] H. No attic access [] F. Other: [] G. Inknown or unidentified [] H. No attic access [] F. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall or the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). [] A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: ; Total roof system perimeter: [] B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft [X] C. Other Roof Any roof that does not qualify as either (A) or (B) above. [X] A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. [] B. No SWR.		
[] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. [] E. Structural Anchor bolts structurally connected or reinforced concrete roof. [] F. Other: [] G. Unknown or unidentified [] H. No attic access [] Mode Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall or the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). [] A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: ; Total roof system perimeter: [] B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft [X] C. Other Roof Any roof that does not qualify as either (A) or (B) above. [A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. [] B. No SWR.		Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. [] E. Structural Anchor bolts structurally connected or reinforced concrete roof. [] F. Other: [] G. Unknown or unidentified [] H. No attic access 5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall on the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). [] A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: ; Total roof system perimeter: [] B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft [X] C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) [X] A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. [] B. No SWR.		
 [] G. Unknown or unidentified [] H. No attic access 5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall on the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). [] A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: ; Total roof system perimeter: Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft [X] C. Other Roof Any roof that does not qualify as either (A) or (B) above. [X] A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. [] B. No SWR. 	bear min [] M both	m, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a imum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or detail connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on a sides, and is secured to the top plate with a minimum of three nails on each side.
 5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). [] A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: ; Total roof system perimeter: Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft [X] C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) [X] A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. [] B. No SWR. 		
 5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). [] A. Hip Roof		nidentified
the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). [] A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: ; Total roof system perimeter: [] B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft [X] C. Other Roof Any roof that does not qualify as either (A) or (B) above. [X] A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. [] B. No SWR.	[] H. No attic access	
Total length of non-hip features: ; Total roof system perimeter: Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft Any roof that does not qualify as either (A) or (B) above. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) X A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR.		
 [] B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft [X] C. Other Roof Any roof that does not qualify as either (A) or (B) above. [A. Swr (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive Swr barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. [] B. No SWR. 	[] A. Hip Roof	
 [X] C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) [X] A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. [] B. No SWR. 	[] B. Flat Roof	Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less
 [X] A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. [] B. No SWR. 	[X] C. Other Roof	
	[X] A. SWR (also ca sheathing or from water in [] B. No SWR.	alled Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling intrusion in the event of roof covering loss.

or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least

Inspectors Initials Property Address 13601 Frigate Ct., Building M, Units 101M-106M, 203M-204M, Clearwater

7. **Opening Protection:** What is the **weakest** form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. **Second**, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings **and** (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart Place an "X" in each row to identify all forms of protection in use for each			Glazed Openings				Non-Glazed Openings	
openi form	ng type. Check only one answer below (A thru X), based on the weakest of protection (lowest row) for any of the Glazed openings and indicate eakest form of protection (lowest row) for Non-Glazed openings.	Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors	
N/A	Not Applicable- there are no openings of this type on the structure		Х	X	Χ		Χ	
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)							
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)							
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007							
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance							
N	Opening Protection products that appear to be A or B but are not verified							
IN	Other protective coverings that cannot be identified as A, B, or C							
Х	No Windborne Debris Protection	Χ				Χ	·	

- [] A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
 - American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
 - Southern Standards Technical Document (SSTD) 12
 - For Skylights Only: ASTM E 1886 and ASTM E 1996
 - For Garage Doors Only: ANSI/DASMA 115
 - [] A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist
 - ☐ A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above
 - [] A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
- [] <u>B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only)</u> All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
 - ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile 4.5 lb.)
 - SSTD 12 (Large Missile 4 lb. to 8 lb.)
 - For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile 2 to 4.5 lb.)
 - □ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
 □ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
 □ B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above
- [] <u>C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007</u> All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

☐ C.1 All Non-Glazed	l openings	classified	as A, B,	or C in the	e table above,	or no Non-Glazed	l openings exist
----------------------	------------	------------	----------	-------------	----------------	------------------	------------------

- ☐ C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above
- ☐ C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials Property Address 13601 Frigate Ct., Building M, Units 101M-106M, 203M-204M, Clearwater

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

FPAT File #MUD2320925

protective coverings not meeting the requirements of "B" with no documentation of compliance (Level N. i.	Answer "A", "B", or C" o					
"B" with no documentation of compliance (Level N in the table above). □ N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist						
☐ N.2 One or More Non-Glazed openings classified as Level D						
table above	137° d 411 1					
 N.3 One or More Non-Glazed openings is classified as Level [X] X. None or Some Glazed Openings One or more Glazed openings 		val V in the table above				
A. None of Some Grazed Openings One of more Grazed of	openings classified and Lev	et A iii tile table above.				
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi						
Qualified Inspector Name: John Felten	License Type: CBC	License or Certificate #: CBC1255984				
Inspection Company: Felten Property Assessment Team		Phone: 866-568-7853				
Qualified Inspector – I hold an active license as a:	(check one)					
Home inspector licensed under Section 468.8314, Florida Statutes training approved by the Construction Industry Licensing Board a						
 □ Building code inspector certified under Section 468.607, Florida S □ General, building or residential contractor licensed under Section 						
Professional engineer licensed under Section 471.015, Florida Sta	tutes.					
Professional architect licensed under Section 481.213, Florida Sta	tutes.					
Any other individual or entity recognized by the insurer as possessing the necessary qualifications to properly complete a uniform mitigation verification form pursuant to Section 627.711(2), Florida Statutes.						
Individuals other than licensed contractors licensed under S						
under Section 471.015, Florida Statues, must inspect the structure structures under s.471.015 or s.489.111 may authorize a dire						
experience to conduct a mitigation verification inspection.	<u> </u>					
I, <u>John Felten</u> am a qualified inspector and I contractors and professional engineers only) I had my employand I agree to be responsible for his/her work.						
k. A						
Qualified Inspector Signature: Date: 12-07-2023						
An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the						
appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector who certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally						
performed the inspection.						
Homeowner to complete: I certify that the named Qualifie residence identified on this form and that proof of identification						
Signature:	Date:					
An individual or entity who knowingly provides or utters a false or fraudulent mitigation verification form with the intent to obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a misdemeanor of the first degree. (Section 627.711(7), Florida Statutes)						
<i>G</i> *** (**** * * * * * * * * * * * * * *						

The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature as offering protection from hurricanes.

Inspectors Initials Property Address 13601 Frigate Ct., Building M, Units 101M-106M, 203M-204M, Clearwater

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.